


## CABO DE AÇO CLASSE 6x19 - USO GERAL COM ALMA DE FIBRA POLIDO OU GALVANIZADO

6x19 CLASS WIRE ROPE - GENERAL USER FIBER CORE - NBR ISO 2408 - UNGALVANIZED OR GALVANIZED

Diâmetro <i>Diameter</i>		Massa aprox. em Kg/m <i>Approximate mass in Kg/m</i>	Carga de Ruptura mínima efetiva em tf <i>Minimum breaking load in tf</i>	
mm <i>mm</i>	Polegadas <i>Inches</i>		IPS (1770 N/mm <sup>2</sup> )	EIPS
3,2	1/8"	0,036	0,61	-
4,8	3/16"	0,082	1,37	-
6,4	1/4"	0,142	2,50	-
8,0	5/16"	0,230	3,90	-
9,5	3/8"	0,343	-	6,10
11,5	7/16"	0,479	-	8,30
13,0	1/2"	0,608	-	10,80
14,5	9/16"	0,775	-	13,60
16,0	5/8"	0,933	-	16,80
19,0	3/4"	1,298	-	24,00
22,0	7/8"	1,805	29,50	32,60
26,0	1"	2,442	38,50	42,60
29,0	1.1/8"	3,055	-	53,90
32,0	1.1/4"	3,733	60,10	66,50
35,0	1.3/8"	4,529	-	80,50
38,0	1.1/2"	5,328	86,50	95,80
45,0	1.3/4"	8,368	-	130,40
52,0	2"	9,740	-	170,30



### CONSTRUÇÕES DA CLASSE

6 X 19 SEALE  
6 X 19 WARRINGTON  
6 X 25 FILLER