


CORRENTES

CHAINS

CORRENTE DE ELOS SOLDADOS GALVANIZADA GALVANISED STEEL CHAIN



REF. CRP	Dimensões				Carga de trabalho kgf	Peso por metro aprox. kg
	D		B	A		
	mm	pol	mm	mm		
CRP-03	3,0	1/8	29	16	125	0,16
CRP-035	3,6	9/64	30	17	200	0,30
CRP-04	4,0	5/32	29	15	225	0,29
CRP-045	4,4	11/64	30	17	250	0,40
CRP-05	4,8	3/16	35	19	350	0,41
CRP-055	5,6	7/32	46	22	450	0,52
CRP-06	6,0	15/64	46	22	500	0,64
CRP-064	6,4	1/4	42	23	550	0,76
CRP-07	7,0	9/32	44	27	600	0,95
CRP-08	8,0	5/16	49	31	625	1,21
CRP-09	9,0	23/64	55	35	700	1,64
CRP-10	9,5	3/8	55	36	800	1,85
CRP-11	11,1	7/16	65	42	1050	2,50
CRP-13	12,7	1/2	76	46	1500	3,12
CRP-14	14,1	9/16	85	51	1900	3,85
CRP-16	15,9	5/8	95	57	2250	5,03
CRP-19	19,1	3/4	114	68	3750	6,97
CRP-22	22,2	7/8	133	80	4825	9,87
CRP-25	25,4	1	152	91	6250	12,68
CRP-29	28,6	1.1/8	171	103	8000	16,34
CRP-32	31,8	1.1/4	190	114	10000	20,24
CRP-35	34,9	1.3/8	210	126	12750	24,39
CRP-38	38,1	1.1/2	228	137	14000	28,84
CRP-41	41,3	1.5/8	248	149	16050	37,00
CRP-44	44,5	1.3/4	267	160	18500	39,49
CRP-51	50,8	2	305	183	24300	51,74