








## CORRENTE DE ELLOS GRAU 8 (NORMA EN818-2 - NBR 1834) GRADE 80 ALLOY CHAIN



Descrição D x T (mm)	Carga máxima de trabalho (kg)	Dimensões (mm)		Peso kg/m	Carga de teste	Carga de ruptura (kg)
		D	T			
6 x 18	1.120	6	18	0,80	2.800	4.480
8 x 24	2.000	8	24	1,40	5.000	8.000
10 x 30	3.150	10	30	2,20	7.875	12.800
13 x 39	5.300	13	39	3,70	13.250	21.200
16 x 48	8.000	16	48	5,70	20.000	32.000
20 x 60	12.500	20	60	9,10	31.250	50.000
22 x 66	15.000	22	66	10,90	37.500	62.000
26 x 78	21.200	26	78	15,20	53.000	84.800
32 x 116	31.500	32	96	23,00	78.750	12.600

Fator de Segurança 4:1  
Acabamento polido oleado

MODOS DE IÇAMENTO CARGAS DE TRABALHO (TF)		1 RAMAL	2 RAMAIS		3 OU 4 RAMAIS		
							
ÂNGULO DE INCLINAÇÃO $\alpha$		0°	0 - 90°	90 - 120°	0 - 90°	90 - 120°	
ÂNGULO DE INCLINAÇÃO $\beta$		0°	0 - 45°	45 - 60°	0 - 45°	45 - 60°	
FATOR DE CARGA SIMÉTRICA		1,0	1,4	1,0	2,1	1,5	
CORRENTE DIÂMETRO NOMINAL		6 mm	1.120	1.600	1.120	2.360	1.700
	8 mm	2.000	2.800	2.000	4.200	3.000	
	10 mm	3.150	4.400	3.150	6.700	4.750	
	13 mm	5.300	7.500	5.300	11.200	8.000	
	16 mm	8.000	11.200	8.000	17.000	11.800	
	20 mm	12.500	17.500	12.500	26.250	19.000	
	22 mm	15.000	21.000	15.000	31.500	22.400	
	26 mm	21.200	30.000	21.200	45.000	31.500	
32 mm	31.500	44.100	31.500	67.000	47.500		