

ESTICADORES EM ALTA CAPACIDADE

HOT DIPPED GALVANISED TURNBUCKLES: US FED SPEC FF-T-791 B



EP3FFGG EP1FFGO

Hot Dipped Galvanized Turnbuckle									
EP3FFGG	EP3FFGG (Gancho x Gancho)								
	EP1FFGO (Gancho x Olhal)								
EP1FFGO	ROSCA (A)	CORPO (B)	Ø CABO	DIMENSÕES Aberto/Fechado		CARGA DE TRABALHO / PESO			
	(Polegada)	(Polegada)	(mm)	(mm)	(mm)	GxG (kg)	Peso (kg)	GxO (kg)	Peso (kg)
06-102	1/4"	4"	3/32"	307	206	181	0.133	181	0.14
08-114	5/16"	4,5"	1/8"	343	241	317	0.214	317	0.226
10-152	3/8"	6"	3/16"	419	267	453	0.325	453	0.340
13-152	1/2"	6"	1/4"	452	300	680	0.646	680	0.680
13-229	1/2"	9"	1/4"	605	376	680	0.753	680	0.793
13-305	1/2"	12"	1/4"	757	452	680	0.938	680	0.988
16-152	5/8"	6"	5/16"	488	335	1020	1.132	1587	1.115
16-229	5/8"	9"	5/16"	640	411	1020	1.292	1020	1.36
16-305	5/8"	12"	5/16"	792	488	1020	1.45	1020	1.474
19-152	3/4"	6"	3/8"	528	376	1360	1.615	1360	1.7
19-229	3/4"	9"	3/8"	681	452	1360	1.938	1360	2
19-305	3/4"	12"	3/8"	833	528	1360	2.477	1360	2.6
19-457	3/4"	18"	3/8"	1138	681	1360	3.016	1360	3.175
22-305	7/8"	12"	1/2"	869	564	1814	3.610	1814	3.8
22-457	7/8"	18"	1/2"	1173	716	1814	4.417	1814	4.65
25-152	1"	6"	5/8"	599	447	2267	3.774	2267	3.973
25-305	1"	12"	5/8"	904	599	2267	4.845	2267	5.1
25-457	1"	18"	5/8"	1209	752	2267	6	2267	6.35
25-610	1"	24"	5/8"	1514	904	2267	7.324	2267	7.71
32-305	1.1/4"	12"	7/8"	963	658	3175	8.19	3175	8.618
32-457	1.1/4"	18"	7/8"	1270	813	3175	10.38	3175	10.93
32-610	1.1/4"	24"	7/8"	1580	970	3175	10.772	3175	11.339
38-305	1.1/2"	12"	1.1/8"	1041	737	3401	11.633	3401	12.246
38-457	1.1/2"	18"	1.1/8"	1346	889	3401	13.442	3401	14.15
38-610	1.1/2"	24"	1.1/8"	1651	1041	3401	16.435	3401	17.33
44-457	1.3/4"	18"	1.3/8"	1504	1046	*	*	*	*
44-610	1.3/4"	24"	1.3/8"	1808	1199	*	*	*	*
51-610	2"	24"	1.5/8"	1948	1339	*	*	*	*
64-610	2.1/2"	24"	2.1/8"	2088	1478	*	*	*	*
70-610	2.3/4"	24"	2.3/8"	2172	1562	*	*	*	*

Fator de Segurança 5 x a carga de trabalho

Corpo e Terminais Forjados em aço carbono
Acabamento galvanizado a fogo